

RECEIVED
CENTRAL FAX CENTER

DEC 07 2006

10/674,705In the claims:

1. (currently amended) A stringed instrument comprising:

a solid body having [~~a~~] exposed front [~~surface~~] and [~~a~~] rear
[~~surface~~] surfaces;

a tuning mechanism;

a neck having one end joined to said body and an opposite end retaining said
tuning mechanism;

a retainer block distinct from and encompassed by said rear surface; and

a plurality of strings each having a first end secured to said tuning
mechanism; and a second end retained by said retainer block.

2. (original) A stringed instrument according to claim 1 including a bridge
mounted on said front surface and wherein said strings extend from said tuning
mechanism, over said bridge, and through said body to said block.

3. (original) A stringed instrument according to claim 2 wherein said
retainer block has an inner surface and an outer surface and defines a plurality of
channels extending between said inner and outer surfaces, and each of said strings
passes through a different one of said channels.

4. (original) A stringed instrument according to claim 3 wherein said second
ends are enlarged to prevent passage through said channels.

10/674,705

5. (original) A stringed instrument according to claim 4 wherein each of said channels comprises a counterbore in said outer surface retaining one of said enlarged second ends.

6. (original) A stringed instrument according to claim 1 wherein said block is unitary and made of brass.

7. (original) A stringed instrument according to claim 6 including a bridge mounted on said front surface and wherein said strings extend from said tuning mechanism, over said bridge, and through said body to said block.

8. (original) A stringed instrument according to claim 7 wherein said retainer block has an inner surface and an outer surface and defines a plurality of channels extending between said inner and outer surfaces, each of said strings passes through a different one of said channels.

9. (original) A stringed instrument according to claim 8 wherein said second ends are enlarged to prevent passage through said channels.

10. (original) A stringed instrument according to claim 9 wherein each of said channels comprises a counterbore in said outer surface retaining one of said enlarged second ends.

11. (original) A stringed instrument according to claim 3 wherein said body defines a cavity retaining said block and intersecting said rear surface.

10/675,705

12. (original) A stringed instrument according to claim 11 wherein said second ends are enlarged to prevent passage through said channels.

13. (original) A stringed instrument according to claim 12 wherein each of said channels comprises a counterbore in said outer surface retaining one of said enlarged second ends.

14. (original) A stringed instrument according to claim 11 wherein said block is unitary and made of brass.

15. (original) A stringed instrument according to claim 14 wherein said second ends are enlarged to prevent passage through said channels.

16. (original) A stringed instrument according to claim 15 wherein each of said channels comprises a counterbore in said outer surface retaining one of said enlarged second ends.